



Klein Marine Systems
Underwater Mission Solutions

KLEIN SYSTEM D3500TF

HIGH-DEFINITION DIGITAL SIDE SCAN SONAR FOR DEEP WATER SURVEYS

The Klein System D3500TF is a digital CHIRP Side Scan Sonar designed for deep water surveys to 3000 m depth. The high fidelity, high definition imaging abilities make the D3500TF system an ideal and versatile tool for various deep water survey applications.

The D3500TF employs a CHIRP transmission mode. Klein's advanced broadband CHIRP signal processing technology coupled with Klein's proprietary display algorithms, provides extraordinary long range, and high resolution seafloor acoustic imagery.

Dual simultaneous frequency (100/400 kHz) operation is standard in the D3500TF. 100 kHz provides long range, 600 m per side, search capability while 400 kHz provides higher resolution imagery for target classification to 200 m range per side.

The System features the new Smart Telemetry which measures the electrical parameters of the tow cable (including slip ring and deck cable) and selects data rate and filter settings that maximize data throughput. This results in continuous, high quality imaging over a broad variety of cable types and cable lengths, in excess of 6,000 meters of 0.68" equivalent cable. This feature is designed to support surveyors and rental companies who frequently switch equipment to different winches and different cables.

The D3500TF operates from 110/230, 50/60 kHz power sources. The standard system configuration is supplied complete with a rugged stainless steel towfish (with heading, pitch, roll & depth sensors installed), a 19" rackmount transceiver processor unit (TPU), a workstation with Windows and SonarPro® software installed, and a 100 m lightweight Kevlar test/tow cable. Available options include; laptop, a depressor wing, a responder interface, a magnetometer interface a motion reference unit, altimeter, and fiber optic tow cable interfaces.



Applications:

- Geology / Geophysical
- Geo Hazard Mapping
- Cable and Pipeline Routing & Inspection
- Archaeological Surveys
- Search and Recovery (SAR)
- Submarine Rescue
- Oceanographic Surveys
- Minerals & Mining
- Benthic Habitat MappingChartin

Key Features:

- Dual, Simultaneous Frequencies (100/400 kHz)
- Depth Rated to 3000m
- Hydrodynamic Stainless Steel Tow Fish
- Optional Magnetometer and Responder Interface Units
- Automatic Variable Rate Bandwidth Telemetry
- Easy Operation

The Difference Is In The Image



KLEIN SYSTEM D3500TF

HIGH-DEFINITION DIGITAL SIDE SCAN SONAR FOR DEEP WATER SURVEYS

Specifications:

System D3500TF Towfish	
Construction	316 Stainless Steel
Body Length	1.94 m (76.4 in)
Outer Diameter	15.2 cm (6.0 in)
Weight (in air / in water)	70 kg (154 lbs) in air 47.7 kg (105 lbs) in water
Maximum Depth Rating	3000 m
Standard Towfish Sensors	Compass: Heading +/- 0.5° RMS Roll and Pitch Sensor Depth Pressure Sensor
Optional Tow Accessories	K Wing II Depressor Wing Responder Interface Magnetometer Interface

Topside Assemblies	
Tranceiver Processing Unit (TPU)	19" rack mount
Workstation PC Windows 7 and SonarPro® Installed	19" rack mount, 21.5" LCD display, keyboard and mouse

System Power Requirements	
Input Voltage	110/230 VAC (50/60 kHz)
Power Consumption	120 w

Side Scan Sonar Specifications	
Technology	Single Beam
Frequency	100 kHz/400 kHz Dual Simultaneous
Pulse Type	FM CHIRP
Horizontal Beamwidth	0.7° @ 100 kHz / 0.3° @ 400 kHz
Vertical Beamwidth	50°
Across Track Resolution	9.6 cm @ 100 kHz, 2.4 cm @ 400 kHz
Maximum Operating Range (per side)	600 m @ 100 kHz, 200 m @ 400 kHz
Vertical Beam Center	Tilted down 20° from horizontal
Output Data Format	SDF (Sonar Data Format), or XTF (Extended Triton Format or both - selectable)



Klein Marine is deeply committed to customer support. We are currently servicing valued customers in 80 countries, and relying on a network of competent International Representatives to meet and exceed the service needs of our customers around the world. We provide 24 hour / 7 day a week support.

For additional information about Klein D3500TF, visit kleinmarinesystems.com or contact us directly.

This technical data and software is considered as Technology Software Publicly Available (TSPA) as defined in Export Administration Regulations (EAR) Part 734.7-11. Specifications subject to change without notice. SonarPro® is a registered trademark of Klein Marine Systems. Cleared for public release. Data, including specifications, contained within this document are summary in nature and subject to change at any time without notice at Klein Marine Systems' discretion. Call for latest revision. All brand names and product names referenced are trademarks, registered trademarks, or trade names of their respective holders. Rev 09/23

KLEIN MARINE SYSTEMS

11 Klein Drive • Salem, New Hampshire 03079

Tel: 603.893.6131 • Fax: 603.893.8807 • Email: kleinsales@kleinmarinesystems.com