



Seamap's SeaLink 24 Channel Tension Module is designed to complement the SeaLink 24 Digital Modules and provide cable tension readings along the cable in the SeaLink 3840 Recording System. The SeaLink 24 Channel Tension Cell Modules are designed to be placed in the head, middle and tail of the cable. Tension readings of each tension module are displayed in real time by the SeaLink 3840 Recording System.

The SeaLink 24 Digital Module is the base building block of the system and is powered via a 750 mA DC constant current loop. The 24 channel analog input is capable of sampling at $\frac{1}{8}$, $\frac{1}{4}$, $\frac{1}{2}$, 1, 2 and 4ms via 24bit delta sigma converters. Digitized data including data from other modules in the array are transmitted to the recording system via Seamap's proven proprietary telemetry system over common electrical twisted pairs. The power, control, data acquisition and systems diagnostics of the modules are performed via the SeaLink workstation on the recording vessel / platform.

The SeaLink 24 Channel Tension Module is enclosed in a 3.0" (76.2mm) OD titanium tube with end-caps. The SeaLink module has a crush depth of 6,925m. The Seamap custom SeaLink 56 pin connector has proven reliable and durable in the harshest environment. All SeaLink Modules have double O-Rings and are Nitrogen filled to ensure mechanical integrity.

The SeaLink 24bit Data Acquisition Systems is based on proven technology and can be configured for many applications including marine seismic data collection.

Custom designs and customizing SeaLink Modules are available upon request. All exposed in-sea metals are titanium.



Key Features:

- 24 Channels in one Module with Tension Cell
- Selectable Gain
- Selectable Low Cut and High Cut Filters
- Lower Power Consumption
- High Channel Capacity – 480 Channels @ $\frac{1}{4}$ ms per Array
- Continuous Data Collection
- Sample Rates of $\frac{1}{8}$, $\frac{1}{4}$, $\frac{1}{2}$, 1, 2 & 4 ms
- Reduced Component Count

Applications:

- Marine 2D / 3D / 4D Seismic
- High Resolution Seismic
- Ultra High Resolution Seismic
- HR3D Ultra High Resolution Seismic
- Ocean Bottom Cable (OBC)
- Vertical Arrays
- Reservoir Monitoring
- Passive Acoustic Seismic

SEAMAP SEALINK™ 24 CHANNEL TENSION MODULE



24 CHANNEL DATA ACQUISITION

Specifications:

SeaLink 24 Channel Tension Module																																		
Tension Cell	1 Cell Per Module	Measurement range: 0 to 20,000 lbs. Measurement accurate over operational range: ± 6%; 0 to 1,200 lbs. Operational Temperature range: 15° C to +71° C (60° F to 160° F), Crush depth: 1524 meters Note: Display in lbs. or Kg																																
Number of Seismic Channels	24 Per Module 4 Data Lines (Programmable Per-Application Requirement)	<table border="1"> <thead> <tr> <th>Rate</th> <th>Int.</th> <th>#Chan</th> <th>#Mod</th> </tr> </thead> <tbody> <tr> <td>8000</td> <td>0.125</td> <td>240</td> <td>10</td> </tr> <tr> <td>4000</td> <td>0.25</td> <td>480</td> <td>20</td> </tr> <tr> <td>2000</td> <td>0.50</td> <td>1,008</td> <td>42</td> </tr> <tr> <td>1000</td> <td>1.00</td> <td>2,016</td> <td>84</td> </tr> <tr> <td>500</td> <td>2.00</td> <td>4,128</td> <td>172</td> </tr> <tr> <td>333</td> <td>3.00</td> <td>Custom</td> <td></td> </tr> <tr> <td>250</td> <td>4.00</td> <td>Custom</td> <td></td> </tr> </tbody> </table>	Rate	Int.	#Chan	#Mod	8000	0.125	240	10	4000	0.25	480	20	2000	0.50	1,008	42	1000	1.00	2,016	84	500	2.00	4,128	172	333	3.00	Custom		250	4.00	Custom	
Rate	Int.	#Chan	#Mod																															
8000	0.125	240	10																															
4000	0.25	480	20																															
2000	0.50	1,008	42																															
1000	1.00	2,016	84																															
500	2.00	4,128	172																															
333	3.00	Custom																																
250	4.00	Custom																																
Non-Seismic Channels Allocated	NAD Channels	Internal Pressure Internal Temperature Voltage Measurements Current Measurements																																
Analog/Digital Converter	24bit Delta Sigma Type																																	
Dynamic Range	> 112 dB (5-206 Hz)	Based on 2ms Sample Rate																																
Distortion	THD < 0.003%	Based on 2ms Sample Rate																																
Lower Power Consumption	Less than 8 watts per module																																	
Preamplifier Type	Voltage Mode Differential Input	Selectable Gain +1.0% accuracy: 0 to 36 dB Increments in 6dB steps																																
Low Cut Filter	Analog	2.5Hz or 5Hz 6db/Oct (Hydrophone Cap + Input Z)																																
Low Cut Filter	Digital Infinite Impulse (IIR) Filter	Selectable Settings: 0.1 to 10Hz in 1 Hz Increments 6db/Oct																																
High Cut Filter	Digital Linear Phase																																	
Selectable Sample Rates	0.125 ms 0.25 ms 0.5 ms 1.0 ms 2.0 ms 4.0 ms	-3 dB Corner Frequency: 3304Hz -3 dB Corner Frequency: 1652Hz -3 dB Corner Frequency: 824Hz -3 dB Corner Frequency: 412Hz -3 dB Corner Frequency: 206Hz Custom																																
Functional Testing	Source: Internal Test Oscillator, Frequency: 31.25 Hz, Sine Wave																																	
Tests	DC Offset, RMS Noise, Channel Gain Accuracy, Impulse Response Hydrophone Leakage, Harmonic Distortion, Crosstalk																																	
SeaLink 24 Digital Module Physical Dimensions	Length: 15.763" (400.38 mm) Overall: 21.233" (539.31 mm) OD: 3.0" (76.2 mm)	Weight in air: 8 lbs (3.629 Kg) Weight in water: 4 lbs (1.814 Kg)																																

Seamap (U.K.) Ltd.

Unit 34, The Maltings, Charlton Estate
Shepton Mallet, Somerset, BA4 5QE, U.K.
Tel: +44 [0] 1749 342223
Fax: +44 [0] 1749 347588
email: seamapsales@mind-technology.com

Seamap Pte Ltd.

51 Changi North Crescent
Singapore 499626
Tel: +65 6545 1054
Fax: +65 6545 0585

MIND Technology

2002 Timberloch Place, Suite 550
The Woodlands, TX 77380
United States of America
Tel: +1 281-353-4475

Seamap (U.K.) Ltd., Seamap Inc., Seamap Pte Ltd (hereafter Seamap) reserves the right to make any changes without notice to any of the products herein at its discretion. Seamap does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights nor the rights of any others. All product names referenced herein are trademarks of their respective companies.
Rev_0424. Copyright © 2002-2024, MIND Technology 11-00-1028-A

